

The image features a large, sleek LED display mounted on a silver, four-legged mobile stand with casters. The display shows a vibrant, high-resolution image of a snow-capped mountain range under a blue sky, with a calm lake in the foreground reflecting the scene. The background of the entire advertisement is a darker, atmospheric version of the same mountain landscape. The Unilumin logo is positioned in the top right corner, and the product name 'UTV SC' is prominently displayed in the center-right. Below it, the text 'LED Conference All-In-One' and 'UTV SC Series' are written in a clean, white font.

*Unilumin*

# UTV SC

LED Conference All-In-One

UTV SC Series



Cinema-Grade Quality

Smooth handling



Remote control



Support nine screen projection



3-in-1 on/off key



Multiple types of interfaces


Smooth Optical Technology



Reduce eye fatigue during viewing



Lightweight design



Hardcore Configuration



Ultra low power consumption



Quick disassembly and assembly



Audio Professional



EBL+  
10000 : 1  
High Contrast



## Three Standard Edition UTV SC Series

**Unilumin**

- Standard 2/4K display
- Standard interface input
- Standby power <0.8W



## UTV SC Series Appearance

Unilumin

- Ultra-narrow bezel · 93% screen-to-body ratio
- 30mm thickness
- Die-cast aluminum material





Unilumin

## Simplify operation with one click



- Internal placement of the Android operating system
- Indicator light shows working status
- Remote control operation, simple and convenient
- A wide variety of signal interfaces



# Smart Screen Casting

Unilumin



- Support 9 screen projection
- Miracast Screen Casting
- Reverse Screen Transfer



# Ultimate Pure Viewing Experience

**Unilumin**



Ultimate Black



50% reduction in reflectivity



Touch No Trace

Pixel surface multi-layer nanoscale processing technology, high contrast, low reflectivity, no longer leaving obvious marks when touched by hand



## Soft Display Light Source

**Unilumin**

Surface light source soft light out  
170° ( H ) / V160° ( V )  
High reliability and stability

- Contrast ratio improved by 3 times
- 50% reduction in reflectivity

EBL+ ( Enhance black level+ ) Multilayer optical processing technology

Contrast ratio can be as high as 10000:1, presenting the ultimate pure black and viewing without reflection, no trace of touch



## Energy Saving and Low Carbon

**Unilumin**




Adopt common cathode design to reduce energy consumption



Adopting RGB full flip design, high utilization of light sources and lower power consumption

# Low Blue Light Eye Protection Mode

- From the original material supply side through the LED blue light chip wavelength screening, effective reduction of blue light hazards, care for eye health ;
- Switching the eye protection mode from the software settings to reduce the damage to the naked eye from prolonged screen viewing;





# Hardcore Configuration

**Unilumin**

- 4\*Cortex-A73+4\*Cortex-A53 Eight-core processing
- WIFI dual-band work, screen casting and Internet access can run simultaneously
- Max 3840\*2160@60Hz
- RS232 (RJ45) serial protocol (TCP) for easy control management
- Support HDCP protocol

# Professional Audio

- Built-in full-range professional audio
- Self-amplifier design
- Frequency response range 90~20KHz

**Unilumin**





## Applicable Scene

**Unilumin**

● Meeting Room

● Report Hall

● Training Room

● Large Classroom



108"

- 2k · 16:9
- Small meeting rooms, training rooms
- 10 ~ 20 people / 10 ~ 30 m²



135"

- 2k · 16:9
- Middle meeting rooms, training rooms
- 20 ~ 50 people / 30 ~ 60 m²



162"

- 2K/4K · 16:9
- Large meeting rooms, training rooms
- 50 ~ 100 people / 60 ~ 90 m²

# Integrated Design

**Unilumin**

- Array-type full front maintenance design, fast installation
- Minimalist structure of 40% compared to traditional LED products
- Flexible installation methods, each size can be wall-mounted or Mobile stand
- Mobile bracket installation as easy and fast as a television set, 2 people can be completed in 2 hours
- Support manufacturers on-site custom structure installation and service





## Quality Assurance

**Unilumin**

- Full front maintenance design
- Module level protection



Anti-collision



Dustproof



Damp-proof



# Specifications

**Unilumin**


Parameter	UTV SC Series				
Model	SC 108	SC135	SC 135	SC 162U	SC 162
Pixel Pitch(mm)	P1.2	P1.2	P1.5	P0.9	P1.8
Package Type	COB				
Brightness	600nit				
Refresh Rate	3840Hz				
Greyscale	13bit				
Contrast ratio	≥10000:1				
Viewing angle	170°(H)/160°(V)				
ROM + Memory	8GB + 64GB				
Maximum power consumption	892W	1360W	1260W	2220W	1790W
Weight	80kg	126kg		180kg	
Visible Area	3.24m²	5.06m²		7.29m²	
Applicable space	10~30m²	30~60m²		60~90m²	



The product has passed domestic industrial tests and received qualification, guaranteeing actual strength and saving your worry in use



FCC



Rhine TUV



CB

# Service Advantages

**Unilumin**

- 1000+ after-sales service outlets, ≤24H door-to-door installation and training services
- WeChat public number proprietary service platform, users can self-service online service or fault reporting
- Standard 2 year warranty, extended warranty can be agreed





# Smart Meetings at Your Fingertips

**Unilumin**

